



LTD Torque Screwdriver

Non-Rotary Adjustable Style - Clicks at Set Torque Value -Torque Value Easily Set with External Scale



*Shown with optional bit

Select proper model according to unit of measure as following color code :

S.I. = Metric = American =

Accuracy ±3%

Model			Torque Range						Overall Length		Weight Approx.	
S.I.	METRIC	AMERICAN	Min.-Max.			Graduation			in.	mm	oz.	g
			S.I.	METRIC	AMERICAN	S.I.	METRIC	AMERICAN				
-	-	LTD24Z	-	-	in.oz 6-24	-	-	in.oz 0.1	3 15/16	-	1 7/8	-
		LTD50Z			15-50			0.25			1 7/8	
		LTD100Z			20-100			0.5			4 5/16	
LTD15CN	1.5LTD	1.5LTD-A	cN.M 2-15	kgf.cm 0.2-1.5	in.lbs 0.2-1.5	cN.M 0.1	kgf.cm 0.01	in.lbs 0.005	3 15/16	100	1 7/8	50
LTD30CN	3LTD	3LTD-A	4-30	0.4-3	0.4-3	0.2	0.02	0.01				
LTD60CN	6LTD	6LTD-A	10-60	1-6	1-6	0.5	0.05	0.025	4 5/16	105	2 7/32	80
LTD120CN	12LTD	12LTD-A	20-120	2-12	2-12	1	0.1	0.05	4 31/32	120	4 7/16	125
LTD260CN	26LTD	26LTD-A	60-260	6-26	6-26	2	0.2	0.1	4 5/8	140	8 13/16	215
LTD500CN	50LTD	50LTD-A	100-500	10-50	10-40	2.5	0.25	0.25	6 1/8	150	11 5/16	320

NOTE

1. For LTD260CN, hook spanner is supplied as standard accessory.
2. For LTD120CN, 260CN, resin grip is supplied as standard accessory.
3. Uses 6.35 (1/4") HEX Bits.